SCRUBBER DRYERS

HEXA MOP SCRUBBER

NEW

Interchangeable batteries

HEXA MOP

Cleaning width	44 cm
Power	2 x 200 W
Surface yield	1320m²/min
Brush rotation speed	140 rotations per minute
Weight without battery or water	21,3 kg
Dimensions (L x W x H)	52 x 45 x 120 cm
Power supply	36V Lithium-ion battery
Autonomy	1h20' maximum
Loading time	1h at 80% - 2h at 100%
Reference	z236h913731

Delivered with 2 standard nylon brushes and 2 batteries.
Other discs and accessories available, contact us.

ENGINES BRUSHLESS POWERFUL

BATTERY AND CHARGER

ULTRA HANDY AND LIGHT

EASY TO USE

FOOT OPERATED

HEXA MATIC SCRUBBER DRYERS

HYPER HANDLING

- Ideal for cleaning swimming pool floors
- Adaptable washing brushes and disc tray
- Delivered with battery + charger + brush

Interchangeable batteries

Hexa Matic M

Cleaning width	ø 40 cm
Power/ brushing speed	175 W/ 150 rpm
Weight	34 kg
Surface yield	1400 m²/h
Brushing	Nylon brush or pad
Detergent/recovery tank	18/ 19 L
Power supply	36 V
Reference	z236f912775

Hexa Matic XL

Cleaning width	ø 45 cm
Power/ brushing speed	300 W/ 100 rpm
Weight	90 kg
Surface yield	1600 m²/h
Brushing	Nylon brush or pad
Detergent/recovery tank	30/ 31 L
Power supply	24 V
Reference	z236f903608

Reference more than 55 models, contact us (single brush, self-propelled).

CORDLESS AIR/WATER VACUUM

HEXA VAC'

NEW

- Eliminate the risk of slips and falls thanks to the absence of cables, ideal for vacuuming up puddles in barefoot areas.

Cleaning in dry or wet mode. Perfect for: vacuuming liquids, emergency leaks, lobbies, changing rooms and toilets. 40 minutes of powerful and constant cleaning, a record on the market.

Engine power	400 W
Weight	9,3 kg
Power supply	Lithium battery (Li-ion)
Water capacity	9 liters
Dust capacity	15 liters
Dimensions (LxDxH)	48 x 36 x 37,5 cm
Reference	z236f916715

Floor squeegee 50 cm

Adaptable telescopic handle.

Cleaning width	50 cm
Reference	NC

CLEANING CENTRAL

Cleaning central

Allows efficient mixing thanks to the 14 color calibrated nozzles. Dilution ratio from 0.5 to 11%. Working pressure: 1.5 to 6 bars. Working temperature: 50°C maximum.
Wall-mounted central unit with 2 products for cleaning/rinsing/ disinfection.
Reference z237fcep2150apa00000
Trolley only for proposed model
Reference z237flb99.chm.sb10

www.myhexagone.com

Dinga type anti-shock gun

Multi-jet gun. Blocking trigger.
Reference qo0001n000

Flexi pro black

Expandable garden hose. ø22 mm anti-twist.
15 m Reference z188f475.500.015
30 m Reference z188f475.500.030

BUDGET, INSTALLATION, USE:

SPOT RANGE: ECO-FRIENDLY PROFESSIONAL VACUUM CLEANERS

TECHNICAL DATA	WIRED SPOT 20	WIRED SPOT 50	WIRED SPOT 100	BATTERY SPOT 150	WIRED SPOT 200
Use	Normal	Normal	Intensive	Intensive	Intensive
Basin area	150 m²	200 m²	300 m²	300 m²	1000 m²
Vacuum cleaner width	40 cm	40 cm	40 cm	40 cm	80 cm
Cleaning speed	from 10 to 15 m/min	from 10 to 15 m/min	from 10 to 15 m/min	from 10 to 15 m/min	from 10 to 15 m/min
Suction power	27 m³/h	27 m³/h	27 m³/h	27 m³/h	27 m³/h x 2
Cable length	18 m	24 m	30 m	5 m	40 m, 50 m optional
Trolley	Yes (supplied)	Yes (supplied)	Yes (supplied)	Yes (supplied)	Yes (supplied)
Filtration capacity	3,1 kg	3,1 kg	3,1 kg	3,1 kg	5,1 kg
Infra red (wall detection)	No	No	2	2	2
Power supply	110 v-240 v / 24 vdc	110 v-240 v / 24 vdc	110 v-240 v / 24 vdc	12V battery - 3h autonomy	110 v-240 v / 24 vdc
Camera	No	No	No	No	No
Weight out of water/in water	7 kg/ 1,3 kg	8,5 kg/ 1,8 kg	9 kg/ 2 kg	9 kg/ 2 kg	19,5 kg/ 5 kg
Minimum water depth	30 cm	30 cm	30 cm	30 cm	30 cm
Page number	20	20	20	20	21

PEPS RANGE: COMMUNITY VACUUM CLEANERS WITH ACTIVE BRUSHING

TECHNICAL DATA	WIRED PEPS 200	E-PEPS BATTERY 200	WIRED PEPS 300 XL	E-PEPS BATTERY 300 XL
Use	Intensive	Intensive	Intensive	Intensive
Basin area	350 m²	350 m²	750 m²	750 m²
Vacuum cleaner width	40 cm	40 cm	60 cm	60 cm
Cleaning speed	from 10 to 12 m/min	from 10 to 12 m/min	from 10 to 12 m/min	from 10 to 12 m/min
Suction power	37 m³/h	37 m³/h	37 m³/h	37 m³/h
Cable length	30 m	5 m	40 m (30 m optional)	5 m
Trolley	In stainless steel (supplied)	In stainless steel (supplied)	In stainless steel (supplied)	In stainless steel (supplied)
Filtration capacity	4 kg of sand	4 kg of sand	6 kg of sand	6 kg of sand
Infra red (wall detection)	1 (wall detection)	1 (wall detection)	1 (wall detection)	1 (wall detection)
Power supply	110 v-240 v / 24 vdc	12V battery - autonomy 3h30'	110 v-240 v / 24 vdc	12V battery - autonomy 3h30'
Camera	No	No	No	No
Weight out of water/in water	14 kg/ 2 kg	14 kg/ 2 kg	17 kg/ 3 kg	17 kg/ 3 kg
Minimum water depth	15 cm	15 cm (Peps) - 40 cm (battery)	15 cm	15 cm (Peps) - 40 cm (battery)
Page number	22	22	22	22

info@myhexagone.com - +33(01) 34 34 11 55

TO EACH THEIR CUSTOM-MADE ROBOT

CHRONO MP3 INOX RANGE: INTENSIVE VACUUM CLEANERS FOR AQUATIC CENTERS

TECHNICAL DATA	CHRONO MP3 M	CHRONO MP3 L	CHRONO MP3 XL	Video camera with screen
Use	Intensive	Intensive	Intensive	
Basin area	400 m²	600 m²	1250 m²	
Vacuum cleaner width	50 cm	60 cm	75 cm	
Cleaning speed	from 10 to 18 m/min	from 10 to 18 m/min	from 10 to 18 m/min	
Suction power	50 m³/h	50 m³/h	50 m³/h	
Cable length	25 to 50 m	25 to 50 m	25 to 50 m	
Trolley	Stainless steel (4 types)	Stainless steel (4 types)	Stainless steel (4 types)	
Filtration capacity	3,1 kg	3,1 kg	3,1 kg	
Infra red (wall detection)	2 or 4	2 or 4	2 or 4	
Power supply	110 v-240 v / 24 vdc	110 v-240 v / 24 vdc	110 v-240 v / 24 vdc	
Camera	Yes (mp4)	Yes (mp4)	Yes (mp4)	
Weight out of water/in water	22 kg/ 3 kg	23 kg/ 3 kg	24 kg/ 3 kg	
Minimum water depth	40 cm	40 cm	40 cm	
Page number	24	24	24	25
				Reference xycmp4

VACUUM RANGE / BIOFILM EXTRACTORS





RANGE FOR NATURAL PONDS

TECHNICAL DATA	DARK CLEANER	VIKING M	VIKING XL	BIOMATIC M	BIOMATIC XL
Use	Buffer tank	Ultra filtration	Ultra filtration	Biopool	Biopool
Basin area	—	350 m²	800 m²	350 m²	1500 m²
Vacuum cleaner width	40 cm	50 cm	75 cm	50 cm	75 cm
Cleaning speed	8 m/min	10 m/min	12 m/min	from 10 to 15 m/min	10 m/min
Suction power	30 m³/h	50 m³/h	50 m³/h	50 m³/h	50 m³/h
Cable length	20 m	25 to 50 m	25 to 50 m	25 to 50 m	25 to 50 m
Trolley	—	Stainless steel pole reel (supplied)	Stainless steel pole reel (supplied)	Stainless steel (2 types)	Stainless steel (2 types)
Filtration capacity	External	3,1 kg	3,1 kg	3,1 kg	3,1 kg
Infra red (wall detection)	1	2 or 4	2 or 4	2 or 4	2 or 4
Power supply	110 v-240 v / 24 vdc	110 v-240 v / 24 vdc	110 v-240 v / 24 vdc	110 v-240 v / 24 vdc	110 v-240 v / 24 vdc
Camera	No	Yes	Yes	Yes	Yes
Weight out of water/in water	14 kg/ 2 kg	22 kg/ 3 kg	24 kg/ 3 kg	22 kg/ 3 kg	24 kg/ 3 kg
Minimum water depth	Buffer tank/40 cm	40 cm	40 cm	40 cm	40 cm
Page number	26	26	26	28	28